



**Specifications Ledvance LED Downlight Biolux DN150 21W 2200lm 60D - 927-965 Tunable White | 175mm - Cutout 160mm - Dali Dimmable - Best Colour Rendering**

[View Product](#)

## General Information

|                          |  |
|--------------------------|--|
| SKU                      | 249875                                 |
| EAN                      | 4099854140310                          |
| Brand                    | Ledvance                               |
| Manufacturer Name        | BIOLUX HCL DL DN150 S 21W TW DALI LEDV |
| Any Lamp all-in warranty | 5 Years                                |
| Average Lifetime (h)     | 40000                                  |

## Technical Information

|                             |                                      |
|-----------------------------|--------------------------------------|
| Technology                  | LED Integrated                       |
| Voltage (V)                 | 220-240                              |
| Dimmable                    | Dimmable with Dali                   |
| Colour Code                 | 927 Extra Warm White, 965 Daylight   |
| Colour temperature (Kelvin) | 2700 Extra Warm White, 6500 Daylight |
| Colour Rendering (Ra)       | 90-99                                |
| Colour of Light             | White                                |
| Light colour options        | Tunable White                        |
| Beam Angle (degree)         | 60                                   |
| Luminous Efficacy (lm/W)    | 105                                  |
| Power factor                | >0.90                                |
| Unified Glare Rating        | < 19 - for offices and schools       |

|                       |               |
|-----------------------|---------------|
| Optical Cover         | Opal          |
| Product Type Category | LED Downlight |

## Fixture Information

|                        |                    |
|------------------------|--------------------|
| Mounting Method        | Recessed           |
| IP-rating              | IP20               |
| Impact Protection (IK) | IK03 - 0.35 joule  |
| Operating Temperature  | -20 to +40         |
| Housing                | Aluminium          |
| Colour of the Fixture  | White              |
| Fixture Connection     | Screwless terminal |
| Series                 | BIOLUX             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 99  |
| Diameter (mm) | 175 |

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

## Why Any-lamp?

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process